



Contact Adhesives

Bostik

Contact Bond

Code	Size	Apply	Qty
G39 BCB1L	1lt	Brush/Roller	10
G39 BCB20L	20lt	Brush/Roller	4

A general purpose, industrial strength contact adhesive, extra strong, water resistant and flexible

Uses: Bonding of Laminates, wood, plastic, leather, rubber metal, concrete and flexible foams

Features: High build adhesive for porous rough or contoured surfaces
Fast touch dry time / One component - no mixing / Heat Resistant
Water resistant and Flexible

Anchorweld 1492

Code	Size	Colour	Apply	Qty
G39 1492CLR20L	20lt	Clear	Spray	1
G39 1492RED20L	20lt	Red	Spray	1

A premium quality, high solids, sprayable polychloroprene contact adhesive

Uses: Use with all current post forming equipment (heated bar or infra red bank heaters)
Boat interiors where laminating or upholstery trimming work is required

Features: N-Hexane safe / High temperature resistant / Excellent atomisation
High early green strength / Excellent working tack life
Easy spray without cob webbing

Anchorweld 1830 / 1831

Code	Size	Colour	Apply	Qty
G39 1830CLR020L	20lt	Clear	Spray / Brush	1
G39 1830CLR200L	200lt	Clear	Spray / Brush	1
G39 1831BLU020L	20lt	Blue	Spray / Brush	1
G39 1831BLU200L	200lt	Blue	Spray / Brush	1

A synthetic rubber based adhesive specifically formulated to bond polystyrene foam

Uses: Pre-fabricated buildings, caravans and mobile homes
Sandwich panels, ceiling tiles and cool rooms

Features: Spray or brush / Fire rated to AS 1530.3 / Fast drying and tack



Contact Adhesives

Anchorweld 2700 / 2701

Code	Size	Colour	Apply	Qty
G39 203CLR020L	20lt	Clear	Spray	1
G39 2701CLR200L	200lt	Clear	Spray	1
G39 203RED020L	20lt	Red	Spray	1
G39 2700RED200L	200lt	Red	Spray	1

A high performance sprayable, polychloroprene, contact adhesive

Uses: Decorative laminates, wood, MDF, particle board, steel, aluminium, plasterboard, natural and synthetic rubbers

Features: Very high early green strength / Heat resistant (120 C+)
Excellent working tack life / High solids content / N-Hexane safe

Anchorweld 2800 FF

Code	Size	Colour	Apply	Qty
G39 2800CLR020L	20lt	Clear	Spray	1
G39 2800CLR200L	200lt	Clear	Spray	1
G39 2800RED020L	20lt	Red	Spray	1

Uses: Bonding rigid flexible polyurethane foams and fabrics, timber, MDF, and particleboard

Features: Fire rated to AS 1530.3-1982 / Rapid drying / Heat resistant (100 C+)
Early foam tear / Low soak - good hold up / Soft glue line

Anchorweld 101 / 101R

Code	Size	Colour	Apply	Qty
G39 10104LT	4lt	Clear	Scraper	4
G39 101R04LT	4lt	Clear	Brush / Roller	4
G39 10120LT	20lt	Clear	Scraper	1
G39 101R20LT	20lt	Clear	Brush / Roller	1

A heavy bodied general purpose polychloroprene based contact spray

Uses: Bonding wood, MDF, particleboard, steel, aluminium, plasterboard, natural and synthetic rubber and flexible polyurethane

Features: High early green strength / N-Hexane safe / high heat resistant
good resistance to oil and petrol / excellent working time