

















Caulk in Colours 450gr

HB Fuller - Caulking Compound

Code	Colour	
G04 FCCBLACK	Black	
G04 FCCBRILWHITE	Brilliant White	
G04 FCCBRNTSIENNA	Burnt Sienna	
G04 FCCCEDAR	Cedar	
G04 FCCCHARCOAL	Charcoal	
G04 FCCFAWN	Fawn	
G04 FCCLIGHTGREY	Light Grey	
G04 FCCLITEIVORY	Light Ivory	
G04 FCCMIDGREY	Mid Grey	
G04 FCCMOCCA	Mocca	
G04 FCCTERACOTTA	Terracotta	
G04 FCCVANILLA	Vanilla	
G04 FCCWARMBROWN	Warm Brown	
G04 FCCWHITE	White	

A premium quality flexible, joint sealant for use in sealing expansion joints and gaps in construction work and tiling.

Uses: Wet area joint sealing / Sealing gaps between baths, basins, splash-backs and tiles
Expansion joints in brickwork, walls and tiles / Sealing around architraves,
window and door frames / Expansion joints around the perimeter of timber floors

Features: Dries 'true' to wet colour / Flexible; $\pm 20\%$ joint movement capability /
Resists long term splitting and cracking / Suitable for vertical and horizontal joints
Paintable / Mould resistant / Interior and Exterior use

Compatible Substrates: Concrete Polyurethane foam / Cement sheeting Plywood
Metal Particleboard / Plasterboard Cement render / Timber Expanded / polystyrene /
Masonry/Brickwork MDF

Clean up uncured sealant with a wet rag and water. Cured material can be removed by
trimming with a knife or scraper