

## Hollow Wall Anchor

Hollow wall anchors are all metal, light duty anchors used for cavity fixing to plasterboard and other hollow wall materials.

Our range accommodates for the maximum material thickness of 38mm.

Uses: Light duty electrical fixings / Light fixtures / Brackets / Hooks

Features: Anti-rotation barbs/spikes built into the flange of the head bite into the installation material and prevent the anchor from spinning



Anti-Rotation barbs / spikes

M4 (1/8 Inch)				
Code	Size	Clearance Hole (diameter)	Material Thickness	Pack Qty
C68 HWA4XS	M4 (1/8)	8mm	1mm-5mm	100
C68 HWA4S	M4 (1/8)	8mm	5mm-10mm	100
C68 HWA4M	M4 (1/8)	8mm	8mm-16mm	100
C68 HWA4L	M4 (1/8)	8mm	16mm-24mm	100

  

M5 (3/16 Inch)				
Code	Size	Clearance Hole (diameter)	Material Thickness	Pack Qty
C68 HWA5S	M5 (3/16)	10mm	5mm-10mm	50
C68 HWA5M	M5 (3/16)	10mm	10mm-16mm	50
C68 HWA5L	M5 (3/16)	10mm	16mm-32mm	50
C68 HWA5XL	M5 (3/16)	10mm	28mm-45mm	50

  

M6 (1/4 Inch)				
Code	Size	Clearance Hole (diameter)	Material Thickness	Pack Qty
C68 HWA6M	M6 (1/4)	11mm	10mm-16mm	50

Zinc Plated material finish  
 Phillips / Slot combination drive

